

## APPENDIX H

### APPLICATION OF THE TELEMETRY ATTRIBUTES TRANSFER STANDARD

<u>Paragraph</u>	<u>Title</u>	<u>Page</u>
1.0	Elements of the Telemetry Attributes Transfer Process .....	H-1

### LIST OF FIGURES

Figure H-1.	Typical elements of the telemetry attributes transfer process.....	H-2
-------------	--	-----

This page intentionally left blank.

## APPENDIX H

### APPLICATION OF THE TELEMETRY ATTRIBUTES TRANSFER STANDARD

#### 1.0 Elements of the Telemetry Attributes Transfer Process

Interchange of telemetry attributes occurs between vehicle instrumentation organizations (the source) and the telemetry ground stations (the destination). Interchange may also take place between ranges. The following are typical elements of this process:

- a. data entry system
- b. source database
- c. export program
- d. interchange medium [this standard]
- e. import program
- f. destination data base
- g. telemetry setup system
- h. telemetry processing equipment.

These elements are depicted in Figure [H-1](#) and are defined as follows:

- 1.1 Data entry system. The data entry system is the source organization's human interface where telemetry attributes are entered into a computer-based system (not affected by this standard).
- 1.2 Source database. The source database is where telemetry attributes are maintained in a form appropriate to the local organization's needs (not affected by this standard).
- 1.3 Export program. The export program converts the telemetry attributes from the source database format to the format defined by this standard and stores them on the interchange medium.
- 1.4 Interchange medium. The interchange medium contains the telemetry attributes being transferred from the source organization to the destination organization. Format and contents are defined by this standard.
- 1.5 Import program. The import program reads the standardized interchange medium and converts the attributes to the destination data base format in accordance with local needs, system characteristics, and limitations.
- 1.6 Destination data base. The destination data base is where telemetry attributes are maintained in a form suitable to the local ground station's needs (not affected by this standard).




Figure H-1. Typical elements of the telemetry attributes transfer process.

1.7 Telemetry setup system. The telemetry setup system accesses the destination database to load the telemetry processing equipment. (Not affected by this standard.)

1.8 Telemetry processing equipment. The telemetry processing equipment is where the attributes will ultimately be used to properly handle the data being transmitted. (Not affected by this standard.)

The interchange medium is intended as a standard means of information exchange. The source and destination organizations are not constrained by this standard as to how the attributes are stored, viewed, used, or maintained.

To use the attribute transfer standard, import and export software must be developed. Once in place, these programs should eliminate the need for test item or project-specific software at either the supplying (source) organizations or the processing (destination) organizations.

**\*\*\*\* END OF APPENDIX H \*\*\*\***