DOCUMENT 451-00



**OPTICAL SYSTEMS GROUP** 

## PHOTOGRAPHY, MOTION PICTURE FILM CORES AND SPOOLS, PERFORATIONS, AND OTHER TECHNICAL INFORMATION

WHITE SANDS MISSILE RANGE KWAJALEIN MISSILE RANGE YUMA PROVING GROUND DUGWAY PROVING GROUND ABERDEEN TEST CENTER NATIONAL TRAINING CENTER

ATLANTIC FLEET WEAPONS TRAINING FACILITY NAVAL AIR WARFARE CENTER WEAPONS DIVISON NAVAL AIR WARFARE CENTER AIRCRAFT DIVISION NAVAL UNDERSEA WARFARE CENTER DIVISION, NEWPORT PACIFIC MISSILE RANGE FACILITY NAVAL UNDERSEA WARFARE CENTER DIVISION, KEYPORT

30<sup>TH</sup> SPACE WING 45<sup>TH</sup> SPACE WING AIR FORCE FLIGHT TEST CENTER AIR ARMAMENT CENTER AIR WARFARE CENTER ARNOLD ENGINEERING DEVELOPMENT CENTER GOLDWATER RANGE UTAH TEST AND TRAINING RANGE

DISTRIBUTION A: APPROVED FOR PUBLIC RELEASE; DISTRIBUTION IS UNLIMITED DOCUMENT 451-00 (Formerly 451-65)

## PHOTOGRAPHY, MOTION PICTURE FILM CORES AND SPOOLS, PERFORATIONS, AND OTHER TECHNICAL INFORMATION

**JANUARY 2000** 

Prepared by

# OPTICAL SYSTEMS GROUP RANGE COMMANDERS COUNCIL

Published by

Secretariat Range Commanders Council White Sands Missile Range New Mexico 88002-5110

This document is available on the Range Commanders Council website at: http://tecnet0.jcte.jcs.mil

## **TABLE OF CONTENTS**

Page

ABSTR	АСТ	v
SECTIO	DNS	
	I Introduction	I-1
I	I Flange Focal Distances	II-1
II	I Timing Displacement	III-1
I	7 Aperture Openings for Cameras	IV-1
v	<sup>7</sup> Light Transmission of Prism Cameras	V-1
APPEN	DICES	
A	Center Hole Specifications, Cores and Spools	A-1
I	S Special Cores and Spools	B-1
(	C Society of Motion Picture & Television Engineers (SMPTE) (Reprints)	C-1
I	ASA Standards (Reprints)	D-1
ł	Perforation Dimensions	E-1

<u>\*Note</u>. Appendix C is reproduced through the courtesy of the Society of Motion Picture and Television Engineers. Appendix D is reproduced through the courtesy of the American Standards Association. This material may not be reproduced from this document.

### ABSTRACT

The information in this document is intended to provide a means of more rapidly identifying most of the cores and spools used throughout the motion picture industry. No attempt has been made to identify all of the various items that are available, but rather to list those items most widely used. Manufacturers' data sheets and/or pamphlets covering this subject for their respective products can be obtained from the specific manufacturer. The pamphlets that apply are Eastman Kodak "16mm, 35mm, and 70mm Films," Pamphlet #P-29 and Photo-Sonics technical data sheets.

## **SECTION I**

## **INTRODUCTION**

The purpose of this document is to present camera technical information and representations of the types of film cores and spools that are currently available on the open market. At the present time, only one company, Eastman Kodak, is supplying the test range industry with these film products. Specific technical information about these products appears in this publication. Additionally, information is included that may be of value to data reduction analysts.

Also provided herein are representations of special cores and spools that are required specifically for high-speed camera use. These specially manufactured devices are designed to withstand the torque generated in high-speed camera operations. In addition to the identification of these cores and spools, an attempt has been made to provide technical information regarding flange focal distances, timing displacement, aperture openings for cameras, and light transmission for prism cameras.

Appendix A of this document contains reprints of cores and spools information that was taken from Kodak Publication P-29. Pictured in appendix B are special cores and spools. Reprints of items relating to film perforation, dimensions, and usage are at appendixes C and D. Specifically, appendix C contains a tutorial on the history, standardization, and usage of various motion picture perforations and the Index to Society of Motion Picture and Television Engineers (SMPTE)-Sponsored American Standards. Appendix D features reprints of two American Standard Dimensions for film perforations. Lastly, reprints of perforation and film dimensions, also taken from Kodak Publication P-29, are in appendix E.

It is recommended that this document be used as an outline to which the user can add the latest information as it becomes known or available.

## **SECTION II**

### FLANGE FOCAL DISTANCES

The information provided in this section could be used to manufacture lens adapters when such adapters are unavailable on the open market. The cost-cutting environment in which the ranges currently operate necessitates varying the use of the present inventory of lenses to meet customer requirements. Most test sites have lenses in their inventory that can be adapted for use on a variety of cameras. An example is the Mamiya M-645, which is normally used with the 16mm Photec V. This lens can be adapted to the Photo-Sonics 4ML and the 4B/4C. With the provided flange focal distances, an adapter can be locally manufactured for these cameras. This configuration produces a very acceptable image as well as good light transmission.

With this information and a real need to use available lenses, a mechanical engineer should be able to implement the local manufacture of an acceptable adapter. The manufacturers of high-speed photographic equipment have shown an interest in the production of these adapters if the development and test prove profitable and a need exists.



### NOTES:

- \_
- 1. All dimensions are at infinity
- 2. "C" Mount dimension .690 (16mm)
- 3. "D" Mount dimension .484 (8mm)
- 4. GSAP Mount dimension 1.0185 (16mm)

PHOTO-SONICS, Incorporated, 1994, Burbank, California.

Back Focus or Flange Focal Distance of Camera Models Currently Used

## <u>16MM</u>

MODEL NO.	A REF	B REF	C REF
-1B	1.796		
-1F	1.635		
Model 6 Thin turret	1.218		
1C	1.796		
1D	1.891		
1E	0.905		
1P	0.69		
1PDL			2.047

## <u>35MM</u>

MODEL NO.	A REF	<b>B REF</b>	C REF
4B-4C	2.274	0.678	2.953
Hasselblad Mount 4B-4C	2.274	0.96	3.234
4E/6E	2.274	0.678	2.953
4M/ML	1	1.953	2.953
Model 5	2.312		
Model 6	2.375	.579	2.953
Mamiya			2.4803
Pentax			1.793

## <u>70MM</u>

MODEL NO.	A REF	B REF	C REF
-10M			3.346
-1B	1.938	1.015	2.953
Hasselblad-5C	1.938	1.296	3.234
-5C	1.625		
-10A	1.938		
Illum. Fiouc10A	2.25	0.703	2.953
-10B	4.594		
-5B	1.938		
-10D	1.5		
-10P	2.25	0.702	2.953
-10R	4.594		
-14			3.347

PHOTO-SONICS, Incorporated, 1994, Burbank, California.

## **SECTION III**

## TIMING DISPLACEMENT

This section contains information primarily of value in the data reduction process. Although the Film Data Recording System (FDRS) has reduced side serial timing to some degree, film edge timing continues to be widely used by the test ranges. Information of this sort is often requested by projects to facilitate their individual data reduction efforts.

Timing Displacement in Reference to Picture



# CAMERA INFORMATION FOR TIMING DISPLACEMENT AT THE TIME THE PICTURE IS BEING EXPOSED, TIME IS BEING PRINTED ON FILM

### TYPE CAMERA

FASTAX WF4S, 16mm FASTAX WF3, 16mm NOVA-FULL, HALF, & QUARTER FRAME, 16mm MILLIKEN, 16mm **REDLAKES FASTAX II** PHOTEC IV, 16mm **REDLAKES HYCAM, 16mm REDLAKES LOCAM, 16mm** PHOTO-SONICS 1PL, 16mm FASTAX WF5, 35 mm FASTAX WF5, HALF FRAME, 35mm **DUMONT STREAK, 35mm** MITCHELL, 35mm **REDLAKES HYTAX, 35mm** PHOTO-SONIC 4B, 35mm PHOTO-SONIC 4C, 35mm PHOTO-SONIC 4E, 35mm PHOTO-SONIC 4ML, 35mm PHOTO-SONIC 10B, 70mm PHOTO-SONIC 10A, 70mm PHOTO-SONIC 10RL PHOTO-SONIC 14S CZR 1VN

### **DISPLACEMENT**

5 perforations before 5 perforations before 3 perforations before 13 perforations after 3.4 perforations after 4.5 perforations before 5 perforations after 26.5 perforations after 13 perforations after 8 perforations before 8 perforations before 7 perforations before 58 perforations before 0 perforation 66 perforations before 44 perforations before 52 perforations before 7.5 perforations before 75 perforations before 4 perforations after 5.5 frames before 14 perforations before 0 frames 10 frames after

## **SECTION IV**

## APERTURE OPENINGS FOR CAMERAS

Although the standards of the American Standards Association are adhered to by most camera manufacturers, some variations in the aperture openings of highspeed cameras may exist. As a rule, these variations do not normally pose problems. However, in scientific photography, aperture openings are critical in computing the field of view. The information that follows is provided to aid in the computation process for critical fields of view.

16MM*	35MM*	70MM*
1PDL296" x .410"	6EL- 1.000" x 1.000"	14S- 2.250" x 2.500"
1VN296" x .552"	4ML- 0.745" x 0.995"	10RL – 2.250" x 2.250"
1PL296" x .410"	4EL - 0.724" x 0.986"	10B - 2.250" x 2.250"
1B - Full frame 16mm	4BL/4CL - 0.745" x 0.995"	10A - 2.250" x 2.250"
Locam - 0.292" x 0.410"	4B/4C - 0.745" x 0.995"	

## Aperture Openings for Cameras

\*<u>Note</u>: Film data recording systems may change aperture opening. Check with manufacturer/manual for this information.

## **SECTION V**

## LIGHT TRANSMISSION OF PRISM CAMERAS

Knowledge of actual light transmission of prism cameras is only required when the light transmission of the camera is less than the light transmission capability of the lens. An example would be to use an f/1.5 lens with a camera that will only allow an f/3.2 light transmission. Any setting on the lens greater than f/3.2 would be negated by the camera.

## ACTUAL LIGHT TRANSMISSION OF PRISM CAMERAS IN USE

16MM	35MM	70MM
PHOTEC V: f/2.8	4B/4C: f/1.9	10B: f/2.2
FASTAX II: f/2.7	4BL/4CL: f/1.9	
WF4S: f/2.7		
HYCAM: f/3.2		

## **APPENDIX** A

# **CENTER HOLE SPECIFICATIONS, CORES AND SPOOLS**

The following excerpts are reproduced by permission of Eastman Kodak Company. Copies of publication P-29, <u>Technical Data of Film Specification</u> <u>Numbers, Spools, Cores, Dimensions and Perforations</u>, may be obtained from Eastman Kodak Company, Department 454, 343 State Street, Rochester, New York 14650.

# CENTER HOLE SPECIFICATIONS

۰.

CONFIGURATION	SPOOL OR CORE	DESCRIPTION
	Туре АА	0.320-inch square center hole with keyway
	Туре Ј	0.324-inch square center hole
	Types R, S, T, U, X, Z	1-inch round center hole with keyway. Note: Type R Core has a key which extends halfway through the center hole
	S-146, S-147, S-148, S-149	0.385-inch round hole with double keyways
	S-65, S-184, S-151	0.385-inch round center drive hole with double keyways and two round drive holes 0.379-inch diameter
	S-83, S-84, R-90, S-101, S-153	0.320-inch square hole with keyway
	R-190	0.320-inch square hole with keyway and two offset round drive holes. One elliptical hole and side 1 and side 2 markings

# CORES AND SPOOLS, 16 mm



**Type T Core**—2-in. O.D., 16 mm. Round center hole with keyway. With film slot.



**Type Z Core**—3-in. O.D., 16 mm. Round center hole with keyway. With film slot.



**R-90 Spool**—16 mm x 100 ft, flange diameter 3.615 in., core diameter  $1^{1/4}$  in. Square hole with keyway in both flanges.\*



**R-190 Spool**—16 mm x 200 ft, flange diameter 4.940 in., core diameter  $1^{1/4}$  in. Square hole with keyway and two offset round drive holes and one elliptical hole in both flanges.\* Side 1 and side 2 markings.



S-153 Spool—16 mm x 400 ft, flange diameter 6.625 in., core diameter  $2^{1/8}$  in. Square hole with keyway in both flanges.\*

\*Center hole configuration aligned on both flanges.

(One foot = .305 metres)

# CORES AND SPOOLS, 35 mm (Continued)

.



Type AA Core—1-in. O.D., 35 mm. Square center hole and keyway. With film slot.



1

Type R Core—2-in. O.D., 35 mm. Round center hole with key extending halfway through center hole. With film slot.



Type U Core—2-in. O.D., 35 mm. Round center hole and keyway. With film slot.



S-83 Spool—35 mm x 100 ft, flange diameter 3.657 in., core diameter 31/32 in. Square hole and keyway in both flanges.\*



S-101 Spool -35 mm x 200 ft, flange diameter 4.625 in., core diameter 31/32 in. Square hole with keyway in both flanges.\*

\*Center hole configuration aligned on both flanges. (One foot = .305 metres)

# CORES AND SPOOLS, 70 mm (Continued)



**Type J Core**—1<sup>1</sup>/4-in. O.D., 70 mm. Square center hole. With film slot.



Type X Core—2-in. O.D., 70 mm. Round center hole and keyway. No film slot.



Type S Core—3-in. O.D., 70 mm. Round center hole and keyway. With film slot.



**S-146 Spool**—70 mm x 15 ft, flange diameter 1.719 in., core diameter 31/32 in. Round center hole with double keyways in both flanges.

**S-147 Spool**—70 mm x 25 ft, flange diameter 2.125 in., core diameter 31/32 in. Round center hole with double keyways in both flanges.



S-148 Spool—70 mm x 50 ft, flange diameter 2.625 in., core diameter 31/32 in. Round center hole with double keyways in both flanges.

(One foot = .305 metres)

# CORES AND SPOOLS, 70 mm (Continued)





S-65 Spool—70 mm x 1000 ft, flange diameter 10.500 in., core diameter  $2^{1/8}$  in. Round center drive hole with double keyways and two round drive holes in both flanges.

\*Center hole configuration aligned on both flanges.

# **APPENDIX B**

# SPECIAL CORES AND SPOOLS

SPECIAL SPOOLS AND CORES for Photo-Sonics Cameras



P/S 1PL 1200' Spool 16mm



P/S 10B 1200' Spool 70mm



P/S 4ML 1200' Spool 35mm



P/S 4B/4C High Speed Core 35mm

## **APPENDIX C**

# SOCIETY OF MOTION PICTURE AND TELEVISION ENGINEERS (SMPTE)

The following reprints are reproduced by permission of the SMPTE. Additional copies may be obtained from SMPTE Headquarters, 9 East 41st Street, New York, N.Y. 10017.

# Motion-Picture Film — Its Size and Dimensional Characteristics

## A TUTORIAL PAPER

### By A. J. MILLER and A. C. ROBERTSON

The dimensions of motion-picture film and the shapes of perforations have followed a logical development over 30 or more years. Traced here is some of this history, so that we can better understand why the American Standards Association recognizes certain standards today. For example, the need for accurate printing processes has led to the introduction of dimensional standards with close tolerances. Improvements in the plastics of which film supports are made, coupled with the use of continuous printers, have led to the introduction of standards which discriminate between products differing only by 0.2% in one dimension, since that small difference is recognized as an important matter in the economical attainment of good quality in printing. Other industry demands have been met over the years: e.g., today's CS perforation (introduced to meet the needs of the CinemaScope development in wide-screen presentation) gives more available area for soundtracks. Also, the 16mm film used today is manufactured slightly narrower than that of earlier years because of improved dimensional stability of the base. Furthermore, the needs of other processes involving films with widths varying from 8mm to 70mm have been recognized in various new standards. It is expected that there will be further changes as the industry develops.

#### Introduction

The purpose of this article is to describe the various forms of perforated film used in motion-picture photography with respect to their history, their standardization, and their usage. There are films of many sizes described in the Index of Standards published annually in the December issue of the *Journal* of the SMPTE. The standards in question describe the dimensions of the films, but do not give a complete background of the origins of the various formats, the way in which they fit a current need, and the relationship to the other formats which may appear to be similar.

It is very difficult for people wanting to do new things to know which is the film of the best size and perforation type that will best suit their needs. In fact, these people may not know what kinds of films are available. Knowledge of this kind is needed to help designers new to the field and at the same time refresh the memory of current practitioners. The required material is scattered so widely that it is prudent and economical to gather it in one place.<sup>1</sup>

In a few cases, such as international standardization, it is helpful also to

Reprinted from: January 1965 Journal of the SMPTE, Vol. 74, pp. 3-11 [1]

Presented on October 15, 1963, to the SMPTE Film Dimensions Committee as a status report, and on September 29, 1964, to the Society's Technical Conference in New York by A. J. Miller, Du Art Film Laboratories, Inc., 245 W. 55 St., New York, N.Y. 10019, and A. C. Robertson, Eastman Kodak Co., Manufacturing Experiments Div., Bldg. 35, Kodak Park, Rochester, N.Y. 14650.

<sup>(</sup>This paper was received in final form on November 2, 1964.)

Copyrighted, 1965, by the Society of Motion Picture and Television Engineers, Inc.

# STANDARDS ADOPTED BY THE SOCIETY OF MOTION PICTURE ENGINEERS FIRST EDITION MAIN OFFICE 712 ELEVENTH STREET N. W. WASHINGTON, D. C. PRICE, 10c EACH \$1.00 A DOZEN

Fig. 1. Cover of pamphlet published by the Society in 1917. It contained 17 titles of standards with brief data about each.

establish the chronological sequence of events, and the history of attempts at simplification. Note in this connection that the numbering of American standards is not sequential. At one time the numbers attached to standards were "used" again for other subjects. This means that the size of the identifying number does not necessarily help set the relative dates for the adoption of standards. Today, however, there is an effort being made to keep the same number for the same item when revisions are made.

When production started in motionpicture photography in the days when

Eastman and Edison worked together in 1889, there was film of one size for positive and negative films. Indeed, for some time there was only one emulsion, and the problem of supply was simple for the photographer and the manufacturer alike. Of course, there were many formats (some of them larger) used in traveling exhibits. Most of these exhibits featured personal appearances, such as those of the lecturing traveller. Some shows were given by men who had previously been magicians. Mèliés and Victor<sup>2</sup> were the best examples. These men were more conscious of the show than of the engineering problems of standardization.

Motion-picture photography has grown and today the list of official standards contains 19 dimensional standards bearing the PH22 number which signifies that they relate to cinematography. Other standards relating to this field are being studied in committee. In addition to the number of film formats which have been recognized in an official sense, there are several specialized or variant formats that have not been officially standardized because they are not employed by enough users to require industry-wide approval. As for the types of emulsions employed, these number several dozen today and range from the relatively simple ones used in making the common black-and-white print stock to the rather unusual emulsions used for color camera-films, color intermediate materials and color print stocks.

There is a wide range of choice of motion-picture films available to the industry as a result of the many combinations of emulsion types, widths, perforations, and pitch dimensions. Accordingly, the question may arise about the need for such variety.

#### Positive and Negative Perforations

There are valid reasons for making film with perforations of different sizes and pitches. However, some film used

January 1965 Journal of the SMPTE Volume 74

in the early days has changed little with respect to format and physical dimensions since Edison's time. The perforations in the earliest film had almost the same size and shape of the current "Bell & Howell" perforation described today by PH22.34-1956. The early film was described in a pamphlet on standardization (Fig. 1) published by the Society in 1917, very soon after the publication of its terms of incorporation and its Bylaws.<sup>3</sup> The perforations described in this booklet had well-defined corners where the round portions intersected the "flats," as shown in Fig. 2 and the lower part of Fig. 3. These corners were not rounded with a fillet and accordingly, the intersections could really be called sharp. As a result of the concentration of stresses permitted by this conformation, fractures were apt to occur in the corners after the film had been projected a few times.

The damage was caused in part by the design of some projectors made in the early twenties. These projectors had many desirable features that brought them into general use. Unfortunately, these projectors also had sprockets of unusual dimensions. The sprockets accentuated the problem caused by perforations which tore at the corners. This tearing came about because of "interference" between the perforations and the entering and leaving sprocket teeth as the film travelled over the sprocket. When the film is pulled forward by the front face of the tooth engaging the front edge of the perforation, and when the film is so short that the trailing edge of the perforation cannot slide down the back face of the entering sprocket-tooth, then the film must tear. The typical tear starts in the comparatively sharp corner of the perforation where the "flat" joined the circular sides.

As a result of unfavorable factors, especially interference, the projection life of the film was sometimes shorter than desired. In 1923, J. G. Jones<sup>4</sup> corrected most of the difficulties con-





Fig. 2. Dimensions for 35mm film as shown in the pamphlet on Standards published by the Society in 1917.

cerning the life of the film by devising the style of perforation still used for 35mm black-and-white release prints. This perforation was rectangular, with rounded corners. His recommendations for the improved style of perforation were proposed in 1923 and adopted by the Standards Committee of the Society in 1928. The primary change was an increase in height of the perforation from 0.073 in. to 0.078 in. This modification was a compromise that made it possible for print film to operate as well in one projector which possessed unusual and actually undesirable design characteristics as in all other projectors. The leeway added by the heightened perforation removed the interference that had caused trouble. Also, the adoption of the rounded corners in the perforation, as shown in PH22.36-1954, was effective in decreasing the stresses in the corners to a safe value. Here we have a special effort aimed at making projectors do

Miller and Robertson: Motion-Picture Film



their best. At that time, even with the addition of another shape of perforation, the supply problems were still fairly easy. In 1923, there were only seven emulsion types used for motion-picture purposes.<sup>5</sup>

#### **Process Photography**

The earliest motion-picture photography was completely straightforward and simple. Complications appeared later with greater use of "process photography" of the inconspicuous kind. At first, process photography was used to produce imaginative scenery or effects, (used as early as 1904 by George Mèliés<sup>6</sup>) also, producers made ghost pictures by double exposure. In a similar way they portrayed people who had such a resemblance to each other

Fig. 3. Dimensions for 35mm film as given in 1930.

that they were regarded as doubles. Sometimes the adventures of twins were recorded in romantic pictures. It was realized later that process photography could be used for other purposes. It was found that realistic background could be printed in by laboratory operations with a process printer, or photographed on the stage by using a regular camera and by having the actors appear in front of a projected image on a translucent screen. These procedures had several advantages, particularly in cost reduction. These operations diminish the need to go on location or to build expensive sets. Process printing and background projection are two techniques included under the general designation of "special effects" photography. Most of these techniques require great accur-

[4]

January 1965 Journal of the SMPTE Volume 74



Fig. 4. Dimensions for 35mm film, both positive and negative, as given in 1934.

acy in the perforating of the film in order to keep at a low value the relative motion between parts of the picture printed at various times. It takes very little relative motion to impair the illusion. Few descriptions of these processes were published before 1928. There have been good descriptions of the traveling matte procedure and other types of process photography since then. A recent article<sup>7</sup> gives a good historical view of the use of these procedures when the industry was young and Norman Dawn was active in devising new schemes. A number of more detailed discussions<sup>8-12</sup> have also been published.

Dawn found that he could not get the requisite accuracy in positioning with most of the cameras available in his day. In 1914, however, a camera with pins fixed solidly to the gate became available, and as a result the reproducibility of positioning the film, necessary for composite photography, became possible. This style of construction is still used today in some cameras. The exact placement of film for successive exposures depends upon the solidity of the registering pins, but it also depends upon the size of the perforation.<sup>13</sup>

The accuracy needed in the control of hole size is exemplified by the tolerances. They are the smallest specified in the standards. Even with good control, it is prudent to make the pins of a process camera larger (and therefore more snugly fitting) than the pins in a studio camera. The studio camera must not

Miller and Robertson: Motion-Picture Film

[5]

make noise, as it might with snugly fitting pins, and so, a small and almost negligible risk of encountering unsteadiness is taken by using pins of nominal size.

#### Search for Accuracy

In spite of the secrecy that surrounded the details of process photography in its early days, film manufacturers were aware that film used for some special operations needed to be perforated more accurately than ever before. Accordingly, the standards were changed so that they indicated tolerable departures from the expected value for some dimensions. Compare Fig. 2 with Fig. 3, which was attached to the report of the Standards Committee in 1930. The film of pioneering days was stated to be 1.375-in. wide without qualification. Later, the same film apparently was considered to be 35 mm wide. The result is that the inch values are stated to the fifth place. Curiously enough, it appears that the dimension describing the pitch is regarded as being basically 0.187 in. in the English system. Accordingly, the metric equivalent is recorded to the fourth place. Even if films are designated 35mm or 16mm, they are not based completely on the metric system. All the PH22 films are hybrids, since they are designed to have 16 frames/ft for 35mm, 40 frames/ft for 16mm, and 80 frames/ft for 8mm film. These dimensions are tied to the use of the sprocket printer generally employed in the United States. Even today we have some trouble in engineering committees in choosing appropriate metric equivalents, and some apparent inconsistencies of dimensioning may still be found. In many cases it is possible to say that the conversions represent acceptable practice and that it is considered that the advantages of having round numbers in both systems outweigh the importance of the residual differences.

It may seem unusual in a country using the foot and inch system to pay a great deal of attention to the metric system. However, motion-picture equipment and film are made in many places all over the world. They are frequently used indiscriminately in combination and these combinations are expected to work together. In fact, they do, for motion-picture standards are among the oldest and most successful in the world.

A standard intended for both negative and positive films was finally adopted in November 1934, and is shown in Fig. 4. It is interesting to see that the tolerances, given only for width in 1930, now are extended to other dimensions, such as hole size, margin, and longitudinal pitch. This was a situation where a special effort was made to get closer tolerances for film used in cameras.

At this time, there was an attempt to eliminate the use of the old negative perforation, described by most users as "Bell & Howell," in favor of the new "positive" perforation. The standard shown in Fig. 4 was specified to be for negative and positive raw stock, thereby, in an attempt at simplification, setting a "universal perforation" as standard. This action considerably preceded the action of the 9th International Congress of Scientific and Applied Photography held in Paris, July 1935, at which time it was proposed that a single perforation be adopted on an international basis. In September 1936, the matter was discussed at Budapest in the meetings of the ISA. The war intervened and ended the The Russians subsequently matter. adopted the perforations with rectangular shape and rounded corners for both negative and positive films. These are the films of Type I and Type Ia tabulated in current proposals<sup>14</sup> of the ISO, which is the successor of the ISA.

However, the individual members of American industry had not asked for this change in practice and were reluctant to act upon the basis of these resolutions. The purchasing agents continued to purchase negative film with "Bell & Howell" perforations. Some European

[6]

January 1965 Journal of the SMPTE Volume 74

standardizing bodies set standards which are obligatory, while American bodies recommend standards to which purchasers or manufacturers need not adhere. The standards merely describe the dimensions of the article which the customer has requested, in keeping with the long established democratic American practice. However, the standards are NOT purchase specifications, and the tolerances represent compromise values set somewhere between the perfection the user would like and the generous range of size the manufacturer would find more comfortable to produce. Actually, a reduction in the size of tolerances, if they are brought below the obvious values needed for a reasonable level of performance and interchangeability, constitutes a basis for competition between suppliers.

In that period of our history, American purchasers continued to order the negative film with the conventional "Bell & Howell" perforations that they had used previously. There were several reasons for their conservatism. One was the cost of getting new equipment after they had just accumulated a great number of cameras and printers. In addition, the libraries of "stock shots" and completed pictures that had been accumulated amounted to millions of feet. It seemed undesirable to go to a new film system using another perforation, which might interfere with the smooth operation of printing operations using the older negatives. Film of the current American standard was serving its purpose admirably.

This episode in the fortunes of an American standardizing body is an excellent example of the position occupied by standards in the United States. The standards do not have the force of law and neither manufacturers nor users are required to follow them. The individuals of the American motion-picture industry refused to follow where the SMPTE attempted to lead by publishing a standard after it had been adopted in committee. As a result of the "universal" standard being ignored, the Society bowed to the desires of the film users in the industry and restored the "Bell & Howell" negative perforation to the standards, where it is today.

The SMPTE standards were reprinted in 1930 and in 1941 in the form of a booklet of American Standards approved during the period of informal cooperation that existed soon after the organization in 1928 of the American Standards Association. By 1938 the relationship became more formal and the format used in the publication of dimensional standards issued by the American Standards Association was similar to the present format (Fig. 5).

These early standards were very brief and, in fact, often stated things by implication. In 1941, the addition of notes became apparent. Until that time, there were few orienting comments. The standards had a formal and conventional structure which sometimes led to misunderstandings.<sup>15</sup> A particularly good example (and a potentially embarrassing item) was the case where Germans and Americans started to use opposite sides for the location of the soundtrack and emulsion for 16mm film!<sup>16</sup>

After 1941, other orienting material, less vital but useful, appeared in appendices. The appendices were not regarded as a substantial part of the standard itself, but as material which would facilitate the use of the standard. Orienting discussions are useful and to a degree they are necessary. There are no textbooks in the field of motion-picture engineering. Accordingly, the notes are the only comments available or the only source of information for the casual reader other than material published by the sales service groups of the film manufacturers.

The preceding discussion has pointed out the way in which standards were written in an effort to help the user get good results. There is a limit as to how far an American group, working as a technical committee, can go in this con-

Miller and Robertson: Motion-Picture Film

[7]



These dimensions and tolerances apply to the material immediately after cutting and perforating.

Fig. 5. Dimensions for 35mm film as given in 1938 when the format of the American Standards Association was developing toward its present shape.

nection. The American Standards Assn. which publishes documents of this kind, is a voluntary association and the standards are not obligatory, as noted above. The standard does not tell him what he can have or must take. Surely, the dimensions must have tolerances chosen so that interchangeability is assured. The standards must also describe the needs of reasonably well-made equipment in current use and its performance. The performance of the resulting filmcamera combination that conforms to these standards must be acceptable. However, the attainment of substantial perfection must be allowed to remain a competitive matter among manufacturers. In any event, it may be said that there is no difference if the customer cannot perceive it in the behavior of the products concerned!

#### "Universal" Perforations

Most prints made in American laboratories have been made on continuous

[8]

January 1965 Journal of the SMPTE Volume 74



Fig. 6. Dimensions for 35mm film as given in 1938 in the form used for positive film.

sprocket-printers, quite unlike the situation in Europe, where step printers are generally employed to make prints. Sprocket printers operate easily and give good results when they are used to make prints by a single exposure.

However, the uniformity of positioning in this printing process does not give consistently reliable results for techniques requiring two or more exposures. When Republic Pictures Corp. began the manufacture of Trucolor prints on either side of a special film stock which had emulsion on both sides, the use of optical printers was considered too expensive. Therefore, step-contact printers were used. Since the 0.073-in. height of the negative perforation was not the same as that of the 0.078-in.

positive perforation, the situation was not improved. Relative movement could take place in a vertical direction, so a remedy was sought. It was found in the use of the "Dubray-Howell" (DH) perforation<sup>17</sup> for the print stock. This perforation had a height of 0.073 in., the same as that used for negative film, and a shape much like the perforations used for negative film, and a shape much like the perforations used for print film. Figure 7 shows the outline of the various perforations, for which the dimensions are given in thousandths of an inch. A printer pin that would fit the "Bell & Howell" perforation would also fit into the DH perforation even though it would make only point contact at the sides.

Miller and Robertson: Motion-Picture Film

[9]



Fig. 7. Outlines of various forms of perforations for 35mm film.

A considerable amount of film thus perforated was printed on modified Duplex printers at Republic. Later, when a new color print film was made as an integral tripack and used more generally, the DH perforation was still employed. Today the most recent style of color print film still employs the DH perforation although it is not regarded as a universal perforation. Not all users are aware of the difference between the perforations on these color prints and the older black-and-white prints. Technicolor changed from the "Bell & Howell" perforation on their imbibition prints to the KS perforation late in 1950, so there is no concurrence in this field.

It is worth recalling that work done in 1937 by the Film Dimensions Committee showed that the film perforated with DH holes gave accurate results and had an adequate projection life. A modified "Bell & Howell" perforation which had round corners was considered seriously for this purpose but was finally dropped.18,19 This perforation resembles the 2mm X 3mm "continental" perforation of Chart 2 of the Standards of the Society, published in November 1934 (Fig. 6). The continental or 2mm X 3mm perforation had been an alternate form listed in the standards as a recognition of European practice. However, perforations of the continental shape were

little used in America and the standard had been effectively superseded by April 1934.

#### Wide-Screen Processes, CinemaScope Perforation

In 1954, a new wide-screen system was announced.<sup>20</sup> This system did not use the wider films employed to produce the Grandeur pictures<sup>21,22</sup> of the 1930's. The new system used camera lenses with special optical properties which gave an anamorphic image on the film. This image, when rectified in projection, gave a more elongated rectangular image on the screen. The use of elongation obtained

wider pictures, within the limitations of ceiling height and other structural features of theaters, and made it practical to project at higher overall magnifications. This system used film that could be processed on conventional 35mm equipment. This new film could be projected on projectors changed so slightly that conventional films could also be employed in them. The projector sprockets were changed so that they would handle the new film as well as the old.<sup>23</sup>

This development was furthered by devising a smaller perforation for the CinemaScope system. The new perforation resembled the DH perforation, but was only 0.078 in. wide. The space made available by narrowing the perforations was taken up by two magnetic stripes placed inside the lines of perforations and two other stripes were placed outside the line of perforations. Even with the added stripes, it was possible to make the projector aperture 0.912 in. wide. This dimension compares favorably with the 0.825-in. width used for the conventional projector aperture. Perforations of the various types are shown in Fig. 7, with the new CS at the lower right.

The height of the projector aperture used in the CinemaScope system is

[10]

greater than that of the conventional sound aperture, so there is a material gain in the use of available area for picture information aside from the apparent gain arising from anamorphosis. The actual heights are 0.600 in. for the sound aperture and 0.715 in. for the new aperture. Recently the use of all four magnetic tracks has decreased and the CinemaScope prints carry "magoptical" tracks which may be played either magnetically, or as photographic soundtracks as occasion demands. The picture aperture is sometimes changed also. A number of these schemes for new formats were studied<sup>24</sup> and used abroad.

#### Cinerama

Another system which gives a much wider picture had been announced a year previous to the presentation of CinemaScope. This earlier system, called Cinerama, used three cameras and three projectors to give a united wide image that created an illusion because of the great amount of peripheral vision that was made possible. The process was an outgrowth of the Fred Waller Flexible Gunnery Trainer<sup>25</sup> used to train aerial gunners to hit fast-moving air-borne targets. The realism achieved in the operation of this trainer was remarkable, and it was thought a civilian produce counterpart could results heretofore not achieved in the field of entertainment.

The film used in this process is conventional 35mm but, in terms of dimensions, it has an unusual feature. The frame is six perforations high. Ordinarily, the height of a 35mm motion-picture frame is four perforations, and the way the film is generally handled cancels some of the errors of perforating. The use of a frame six pitches high, when the film is perforated four pitches per frame might be expected to destroy the cancelling effect<sup>26</sup> and give rise to some unsteadiness. However, film is manufactured more accurately today than previously and the use of cancellation in projection is not a vital factor where the extreme accuracy of process photography is not needed. In fact, cancellation is not very effective if the errors of camera, printer, or projector are greater than the errors of perforation. The Cinemiracle process, which was evolved several years later, resembles Cinerama.

#### VistaVision and Technirama

These two systems produced a larger picture than that employed in the conventional 35mm system, but achieved it by employing a 35mm frame twice as big or eight perforations long. The film was moved horizontally, which explains the name of "lazy eight" that was sometimes applied to the VistaVision process. The prints at first were made by contact, and used for projection in especially equipped theaters. However, most negatives were printed optically in various used 35mm formats in more conventional projectors.

The advantages of these two systems were to be found in the use of film of traditional size, which is easily purchased and developed, and in the use of a large negative area. The use of film in the horizontal position had been tried several times before, but these systems were the only ones that reached commercial proportions. Printing from larger formats thus obtained in the negative leads to a reduction of grain in the print. This decrease in the effective granularity of the negative makes the use of larger negative formats attractive. One of the disadvantages of the VistaVision process possibly was connected with the comparative large acceleration which had to be used (especially in the projector) to move the 35mm film a distance of 1.496 in., compared to a distance of only 0.935 in. required for the 70mm format. Thus, the advance of the film needed for the "lazy eight" was 60% greater than that needed for the wider film. However, the area (or weight) of the 70mm film was 25% greater than that of the 35mm film VistaVision format.

Miller and Robertson: Motion-Picture Film

#### CinemaScope 55

Film 55.625mm wide was employed in the camera for a while in order to achieve reduction of grain in 35mm prints having the CinemaScope format. However, there are no productions in the market today which use this format.

#### 70mm Wide Screen Process

Other systems have been used in order to give the viewers a sense of participation, or to reduce the effect of graininess in the projected print. Among these are MGM Camera 65, Panavision, Super Technirama, and Todd A-0, all of which use 70mm release prints.<sup>27</sup>

There is one size of 65mm film in current use, which is employed as a negative film.<sup>28</sup> However, there are three types of 70mm films, only one of which is used currently for motion pictures. Obviously, caution must be used in ordering the proper film.

One 70mm film was derived from the old "Grandeur" film used in the 1930's and is not used for motion-picture work today. It is described by PH1.20-1963<sup>29</sup> as Type I and designated in that standard as something not intended to be used in motion-picture photography. It has a longitudinal pitch of 0.234 in. rather than the usual 0.187 in. It uses larger perforations than other films. Today this film is used mainly in recording and a few styles instruments of special-purpose data-recording cameras, some of which can be considered as motion-picture cameras, although not used in making entertainment films. These cameras are used in gathering data concerning measurements. Another size of film which conforms to PH1.20-1963, but is designated as Type II, was formerly described by a Military Standard. This Type II film has a margin of 0.079 in. and perforations of the usual KS conformation. It is used largely for aerographic purposes and for still pictures in the Graflex combat camera which is built for cassette loading with an expendable magazine.

The 70mm film described first, which is the one used today for current motion picture print<sup>30</sup>, is new. It is unusual because it has the perforations of the 65mm negative<sup>28</sup> with extra film added to the region outside the perforations (as it were) in order to make room for several magnetic soundtracks. The picture frame is five perforations high. This arrangement was requested originally in order to get the desired proportions. Also, this time it was planned to make the prints in projection printers with considerable care in order to get maximum steadiness of image. The process of optical printing also allowed a calculated distortion of the image to be accomplished, the distortion offsetting that which might be expected to take place during later projection on curved screens, and at considerable angles of inclination. This procedure of making special prints was expected to give the least possible distortion of tall objects visible on the screen of a particular theater. Uncorrected prints are currently being made by contact on a sprocket printer, with satisfactory results. It is expected that there will soon be a new proposed standard for negative film to be printed by contact. Such a proposal will differ from the present one in that it will have a slightly different longitudinal pitch.

#### **Amateur Movie Films--Small Films**

The use of the old standard 35mm film has been supplemented to some extent by 70mm film which is used to produce bigger images, at a bigger cost. This procedure can be justified for certain pictures exploited in luxurious theaters.

Amateurs, obviously, cannot afford costly film for their home movies. This is the reason that when an amateur movie system was announced by Mees,<sup>31</sup> the 16mm size was chosen as a good compromise between cost and utility. In addition, there was another consideration in respect to protection from fire. It was thought that some small

[121

January 1965 Journal of the SMPTE Volume 74

operators might want to make 16mm film from 35mm film which, at that time was coated on flammable nitrate film base. The l6mm size could not economically be cut from perforated 35mm film, a fact which afforded a certain degree of protection against this contingency. It has been a strong tradition in the American film industry that 16mm and 8mm film must always be coated on safety film base.

The use of reversal processing obviated the need for making prints and thus kept prices low. In addition, the use of controlled second exposures in processing gave images which were uniform in density in spite of variations in exposure or emulsion thickness. The pictures were astonishingly free from graininess. All these advantages resulted in success for the 16mm system, which had not been attained by the 30 or more systems12 previously intended and exploited for amateur use.

The dimensional standards for this 16mm fil<sup>33</sup> were announced soon after the film was introduced. This was quite unlike the situation where 35mm film was standardized some time after commercial utilization. The dimensions of 16mm film have remained largely unchanged over the years, if we except the narrowing of the width, and the shortening of the pitch for professional camera original film. These changes had to be made to offset the effects of decreased shrinkage that took place when the film base was improved.

Actually, the "amateur" 16mm film has changed character. Very excellent equipment is made for this format which is employed extensively today as a medium for professional use. Today the amateur generally uses 8mm film; this smaller size was made possible by improvements in the graininess of emulsions. The dimensions of the film<sup>34</sup> have not changed much since they were published as DS8-1-1 and as the proposal for Z22.23 in 1938. However, the film actually came into use in 1932. In recent years, 8mm projectors<sup>35</sup> have been provided with magnetic soundtracks<sup>36-38</sup> which later were standardized<sup>39</sup> with test films provided for them. There has also been talk of producing photographic sound on film of this size.

The cost of processing narrow films has been a problem, since the length is large compared to the area. Accordingly, the cost of labor and equipment required to handle it is greater than one would like. The problem was met in the 8mm system by making the camera film a "double 8" or 16mm in width. In the 16mm field, the 32mm print  $film^{40}$  is analogous. Also, there is 35mm film perforated 32mm<sup>41,42</sup> which allows the laboratory to use its developing equipment to produce both 16mm and 35mm sizes. Eventually there will be a proposal for 35mm film to be perforated 8mm with five rows of perforations, which subsequently will be split to form four strips of 8mm prints.

In recent years, there has been much interest in new, small film formats with special reference to their use in education. Information on this subject is contained in sections on nontheatrical films and 8mm cinematography of the Progress Committee Reports for 1962, 1963, and 1964, in the May 1963, 1964 and 1965 issues of the Journal.

#### **Problems of Printing**

Thus far, the films described have been of considerably different sizes, and little mention has been made of films which differ only slightly from each other and serve in a special complementary relationship.

Such paired films are made up of a developed and edited negative, and the positive raw stock to be printed from it. Formerly, the original dimensions of the two films could have been the same at the start or at time of manufacture. The reason that this near identity of dimensions could be used was that the prints might have been made by a

#### Miller and Robertson: Motion-Picture Film

[13]

ARRANGEMENT FOR CONTINUOUS CONTACT PRINTING



Fig. 8. Schematic of a sprocket printer showing the relationship that necessitates a shorter pitch if the negative is not to slip during exposure.

process wherein the separate frames were exposed one by one in a "discontinuous" process of step printing. In such a case, the exact size of the longitudinal pitch within limits - would not matter. If printing was done by a continuous process, it would be done from negatives that had shrunk during the time normally used for editing. Accordingly, the negative had attained a shrinkage which satisfied the demands imposed by the geometry of the process.

Continuous printing is generally done on a device having a sprocket, as shown schematically in Fig. 8. This arrangement requires that the pitch of the negative, which is placed on the inside of the pair of films, must be shorter than the pitch of the print stock. The latter is, of course, the one placed on the outside of the pair of films.

If the proper difference of pitches were not accomplished, the actual surface speed of the films, which are fed over the printing drum by the sprocket teeth pitch by pitch, would not be the same. In that case, there would be differential movement between the two pieces of film. Slippage would take place. The result would be blurring of outlines, particularly parallel horizontal lines, and a general feeling on the part of an observer that sharpness had been lost. Sometimes the adjustment of lengths that occurs when there is a poor matching of pitches is delayed for several frames. A rather large jump is the result. Not only does slip affect the quality of pictures, but it has a bad effect upon sound as well.

The sprocket teeth are not indicated in Fig. 8, but the neutral surfaces of the film are shown. These are the regions about which bending takes place without a change taking place in their length. These neutral planes are the ones from which calculations are made. In bent film, the portion of film lying inside the neutral surface is slightly compressed, and the portion outside is slightly stretched.

For best results, the difference in pitch can be calculated if we know the thickness of the film and the dimensions of the printing sprocket. The difference in pitch which gives nonslip printing is the ratio of the thickness of the film to the radius of the sprocket corrected for the added film thickness. The optimum value is close to 0.3% for a sprocket 1 ft in circumference. Observe that the ratio is, more precisely, the film thick



ness divided by the value representing the radius of the base circle increased by half the thickness of the inner film.

Negatives made with the safety film base used today do not shrink 0.3% while stored during the time needed for editing. In fact, since 1950, the negatives generally used do not shrink the 0.2% that would give tolerable results at the lower level of pitch differential. Some corrective action is needed. Accordingly, the pitch of negatives made on the improved safety film bases available today, must be shortened ahead of time.<sup>43</sup>

The amount of shortening that is necessary is indicated in Fig. 9 which shows an experimental verification of the value required by geometric theory.<sup>44</sup> Streiffert's later data,<sup>45</sup> when plotted, gave similar results. These data describe measurements of flutter made on sound recordings.

The ordinates in Fig. 9 show the ratings given by a jury for a number of prints made from negatives of different pitches. The ratings are actually demerits, and hence, the lower the value the better the performance. The demerits are stated on a five-point scale, where E represents the worst prints ever seen and A represents the best.

In some of the experiments, the negatives were perforated to a shorter pitch than the normal value; in other cases, the difference in pitch was secured by aging procedures. In all cases, the pitch differential in percentage values is shown as abscissae. The dotted vertical lines show the acceptable range of privileged prior opinion of individuals examining prints in review rooms. The range of values seems well chosen and the mean agrees with the value chosen from geometric considerations. There is a certain amount of scatter in the location of the points, but the minimum value is easily decided upon and is very close to the calculated value of 0.3%. The results show a loss of one letter-rating point, going from 0.3% pitch differential up to 0.4%, or down to a differential of 0.2%.

A description of this relationship between positive and negative films is given briefly in the Appendix of Per

Miller and Robertson:

**Motion-Picture Film** 

[151

forating Standards. An example is to be found among the several proposed Standards published in the September 1963 issue of the *Journal*. The standards cited are for 35mm film perforated KS-1870, and for 35mm film perforated DH-1870. These are examples of print stock.<sup>46,47</sup> The same issue of the *Journal* contains a proposal for 35mm film perforated BH-1866<sup>48</sup> which is the best example of film used for camera negatives.

The task of identifying film perforations properly has grown more difficult as the variety of perforation types has increased. The use of identifying letters such as BH and KS used in the paragraphs above was started recently."

The system is being extended so as to describe the more elaborate specialpurpose films frequently used to decrease the cost of printing 16mm or 8mm film, or to decrease the need for another set of developing tanks in the laboratory.

#### **Problems of Developing and Later Use**

Vexatious problems often arise when someone who sets up a new venture in picture-taking does not consider the subsequent steps. For instance, 35mm film perforated 32mm, cannot be developed on 35mm machines made with sprockets designed to fit 35mm film perforated KS-1870; a sprocketless developing machine must be used. If this machine is not available locally, then the exposed material must be shipped away for development. The added expense may not be a crucial matter, but the delay is often very troublesome.

Similar troubles could be encountered in the use of 70mm film existing in several formats. Indeed. while there is a considerable choice of equipment for motion-picture films of conventional width and frame-size, there is little choice (and sometimes none) for equipment designed to handle the unusual format. Sometimes equipment has to be made to special order, which is an expensive and slow process.

#### Summary

In this paper the authors have attempted to show the progress of the art of making motion pictures, and the problems of standardizing the dimensions of the resultant products. In the beginning, there was a tendency to produce films of different sizes because of lack of contact between the entrepreneurs,<sup>50</sup> or even because of a kind of pride in having something different. However, most of the recent changes have been made with good reason. One example is the saving of area in the CinemaScope process, which also permits peripheral viewing of the projected image. Another example of a defensible change is the use of the 70mm process to reduce the effect of graininess observed in the projected print, or to get more light on the screen. As a result of the adoption of these new sizes, there are a number of sizes available to designers who want to develop equipment for new purposes.

In addition to a knowledge of the geometry underlying the design of a sprocket printer, a good understanding of the printing operation requires some knowledge of the changes taking place in the size of film with the passage of time and also with changing conditions of storage. For example, film can undergo changes that are reversible, as when it is heated. Under these conditions, it expands; when it is cooled, the film contracts again as do most other materials. Similar changes in dimensions take place when film is taken from surroundings of a given humidity and then put into a moister atmosphere. The film will swell, just as wood does, and will shrink when it is changed to drier surroundings. The size of these reversible changes can be typified by making measurements and then calculating the thermal and humidity coefficients. These values give the fractional change in size in terms of

[16]

January 1965 Journal of the SMPTE Volume 74

percentage change per degree Fahrenheit or changes with respect to the percentage relative humidity.<sup>51</sup>

There are also changes in size which take place over a greater length of time because the solvents have left the film. This change in size is, of course, shrinkage. This is an irreversible change. The extent of long-term shrinkage has decreased over the years, but it still is a factor to be reckoned with if the operator intends to make prints from old negatives.<sup>52-54</sup>

Data about long-term shrinkage are also of interest in connection with projection practice. However, in current American practice, shrinkage is seldom so great that the operation of the projector is impaired. An exception can be found in unusual equipment (including cameras) where the film occupies too great a "wrap" around a sprocket thereby bringing into use more teeth than may be necessary. Arbitrarily, and as a start for discussion, the greatest number of teeth in engagement may be set at six. The engineering principles have been discussed<sup>55</sup> and set forth in a recommended practice<sup>56</sup> which should be consulted for quantitative discussion.

This paper outlines the need for dimensional accuracy and comments upon the notes and appendices to standards which serve as sources of information in a field where there are no textbooks.

Acknowledgment is made to many colleagues in the Film Dimensions Committee, in the industry, and in our own organizations who have helped us in this work.

#### References

- Loyd A. Jones, "A historical summary of standardization in the society of motion picture engineers," Jour. SMPE, 21: 280-293, Oct. 1933.
- Samuel G. Rose, "Alexander F. Victor motion-picture pioneer," Jour. SMPTE, 72: 614-621, Aug. 1963.

- Glenn E. Matthews, "A note on the early history of the Society and its work on standardization," Jour. *SMPTE*, 72: 196-202, Mar. 1963.
- J. G. Jones, "Film sprocket design," Trans. SMPE, No. 17: 55-74, Oct. 1923.
- C. E. Kenneth Mees, "History of professional black-and-white motion-picture film," Jour. SMPTE, 63: 134-137, Oct. 1954.
- Maurice Bessy and Lo Duca, Georges Melies, Mage, Jean-Jacques Pauvert, 1961
- Raymond E. Fielding, "Norman 0. Dawn: pioneer worker in special-effect cinematography," Jour. SMPTE, 72: 15-23, Jan. 1963.
- Ray Kellogg and L. B. Abbott, "Some special photographic effects used in motion-picture production," Jour. *SMPTE*, 64: 57-61, Feb. 1955.
- 9. Zoli Vidor, "An infrared self-matting process," Jour. *SMPTE*, 69: 425-427, June, 1960.
- Raymond E. Fielding, "Special-effects cinematography: a bibliography," Jour. SMPTE, 69: 421-424, June, 1960.
- 11. J. A. Norling, "Trick and process photography," Jour. SMPE, 28: 136-157, Feb. 1937.
- Walter Beyer, "Travelling matte photography and the blue-screen system," published serially, Am. Cinemat., 44: 590-606, Oct. 1963; 45: 34-45, Jan. 1964; 208-210, 226-227, Apr. 1964; 226-268, 288-290, May 1964; 502-504, 522-524, Sept. 1964; 564-568, 592-594, Oct. 1964. Presented on April 16, 1964, at the 95th Technical Conference of the SMPTE in Los Angeles and scheduled for publication in a forthcoming issue of the Journal of the SMPTE.
- 13. A. C. Robertson, "Pin registration," Jour. SMPTE, 72: 75-81, Feb. 1963.
- Alex E. Alden, "International standardization," Jour. SMPTE, 71: 32-37, Jan. 1962.
- E. K. Carver, "Errors of interpretation and clarity in motion-picture standards," Jour. SMPTE, 66: 530-533, Sept. 1957.
- 16. Reports of Committee on Standards and Nomenclature, Jour. SMPE, 23: 3-5, July 1934.
- A. S. Howell and J. A. Dubray, "Proposed changes in the present standard of 35mm film perforations," Jour. SMPE, 20. 503-511, Apr. 1933.
- W. G. Hill, "Modified negative perforation proposed as a single standard for 35mm negative and positive motion-picture film," Jour. SMPTE, 57: 108-123, Aug. 1951.
- R. W. Lavender, "Photoelectric method for evaluating steadiness of motion-picture film images," Jour. SMPTE, 57: 124-130, Aug. 1951.
- 20. Earl I. Sponable, H. E. Bragg and L. D. Grignon, "Design considerations of Cinema-

Miller and Robertson: Motion-Picture Film [17]

Scope film," Jour. SMPTE, 63: 1-4, July 1954.

- Progress Committee Report on Films and Emulsions, Jour. SMPE, 14: 225-226, Feb. 1930.
- 22. A. S. Howell and J. A. Dubray, "Some practical aspects of and recommendations on wide-film standards," Jour. SMPE, 14: 59-84, Jan. 1930.
- American Standard Dimensions for 16 Tooth 35mm Motion-Picture Projector Sprockets, PH22.35-1962, Jour. SMPTE, 71: 370, May 1962.
- American Standard Dimensions of Four Track Magnetic Sound Records for 35mm. Release Prints, PH22.137-1963, Jour. SMPTE, 73: 23, Jan. 1964. H. Tummel "Die Geschichte der Bildformate in der Kino-Technik," Kino-Technik, May 11, 1955.
- Fred Waller, "The Waller flexible gunner trainer," Jour. SMPE, 47: 73-87, July 1946.
- R. P. Shea, "Procedures of registration in process photography," Jour. SMPTE, 64: 559-560, Oct. 1955.
- 27. Wide-Screen Motion Pictures, SMPTE Pub lication (now in process of revision).
- American Standard Dimensions for 65mm Motion-Picture Film, KS-1870, PH22.118 1961, Jour. SMPTE, 70: 189, Mar. 1961.
- American Standard Dimensions for 70mm Unperforated and Perforated Film for Cameras Other than Motion-Picture Cameras, PH1.20-1963.
- American Standard Dimensions for 70mm Motion-Picture Film, Perforated 65mm, KS-1870, PH22.119-1961, Jour. SMPTE, 70:190, Mar. 1961.
- C. E. K. Mees, "A new substandard film for amateur cinematography," Trans., SMPE, No. 16: 252-258, May 1923.
- 32. G. E. Matthews and R. G. Tarkington, "Early history of amateur motion-picture film," Jour. SMPTE, 64: 105-116, Mar. 1955.
- American Standard Dimensions for 16mm Film Perforated Two Edges, PH22.5-1953, (now under revision), Jour. SMPTE, 62: 84, Jan. 1954.
- American Standard Dimensions for 8mm Motion-Picture Film, PH22.17-1954, Jour. SMPTE, 62: 390, May 1954.
- J. M. Calhoun, Progress Committee Report, section on 8mm cinematography, Jour. SMPTE, 72: 370-372, May 1963.
- Marvin Camras, "Magnetic sound for 8mm projectors," Jour. SMPE, 49: 439-452, Nov. 1947.
- Business Week, "Fairchild breaks sound barrier in 8mm movies," 70-72, Jan. 30, 1960.
- 38. R. J. Roman, J. M. Moriarty and R. B.

[18]

Johnson, "A new magnetic sound projector," Jour. SMPTE, 69: 882-886, Dec. 1960.

39.American Standard Dimensions of Magnetic Striping of 8mm Motion-Picture Film, Perforated 1R-1500, PH22.88-1963, Jour. SMPTE, 72: 493, June 1963.

American Standard Specifications for 8mm Flutter Test Film, Perforated 1R-1500, Magnetic Type, PH22.128-1962, Jour. SMPTE, 71: 855, Nov., 1962.

American Standard Specifications for 8mm Azimuth Test Film, Perforated 1R-1500, Magnetic Type, PH22.129-1962, Jour. SMPTE, 71: 866, Nov. 1962.

American Standard Specifications for 8mm 400-Cycle Signal Level Test Film, Perforated 1R 1500, Magnetic Type, PH22.130-1962, Jour. SMPTE, 71: 857, Nov. 1962.

American Standard Specifications for 8mm Multifrequency Test Film, Perforated 1R-1500, Magnetic Type, PH22.131-1962, Jour. SMPTE, 71: 858, Nov. 1962.

- American Standard Dimensions for 32mm Motion-Picture Film, 2R-3000, PH22.71-1957, Jour. SMPTE, 66: 134, Mar. 1957.
- 41. W. H. Gephart, Jr., "The use of 35/32mm films for the production of 16mm black-and-white or color prints," Jour. SMPTE, 66: 97-99, Mar. 1957.
- 42. Proposed American Standard Dimensions for 35mm. Motion-Picture Film, Perforated 32mm, 2R-3000, PH22.138, Jour. SMPTE, 71: 592, Aug. 1962.
- Charles R. Fordyce, "Improved safety motion-picture film support," Jour. SMPE, 51: 331-350, Oct. 1948.
- 44. A. C. Robertson, "Film standards, film dimensions, and film behavior," a paper presented at the Society's 63rd Technical Conference in Santa Monica, May, 1948.
- 45. J. G. Streiffert, The radial tooth, variable pitch sprocket, Jour. SMPTE, 57: 529-550, Dec. 1951.
- 46. Proposed Revision of American Standard Dimensions of 35mm. Motion-Picture Film, DH-1870, PH22.1, Jour. SMPTE, 71: 674, Sept.1962.
- Proposed Revision of American Standard Dimensions 33mm. Motion-Picture Film, KS-1870, PH22.36, Jour. SMPTE, 71: 675, Sept.1962.
- Proposed American Standard 35mm Motion-Picture Film BH-1866, PH22.93, Jour. SMPTE. 71: 676, Sept. 1962.
- Henry Kogel, "Titles of standards on film dimensions," Jour. SMPTE, 66: 74, Feb. 1957.
- 50. C. L. Gregory, "The early history of wide films," Jour. SMPE, 14: 27-31, Jan. 1930.
- 51. Eastman Motion-Picture Films for Professional

### January 1965 Journal of the SMPTE Volume 74

Use, 3rd ed., p. 10, Eastman Kodak Co., Rochester, N.Y., 1958.

- 52. C. R. Fordyce, J. M. Calhoun, and E. E. Moyer, "Shrinkage behavior of motion picture film," Jour. *SMPTE*, 64: 62-66, Feb. 1955.
- 53.P. Z. Adelstein and J. M. Calhoun, "Inter pretation of dimensional changes in cel lulose estar base motion-picture films," Jour. SMPTE, 69: 157-163, Mar. 1960.
- 54. Storage and Preservation of Motion-Piciure Film, Eastman Kodak Co., Rochester, N.Y.
- 55. J. S. Chandler, D. F. Lyman, and L. R. Martin, "Proposals for 16mm and 8mm sprocket standards," Jour. *SMPTE*, 48: 483-520, June, 1947.
- Committee on Standards Report, "Recommendations for 16mm and 8mm sprocket design," Jour. SMPTE, 54: 219-228, Feb. 1950.

## Index to SMPTE-Sponsored American Standards and **Recommended Practices** JANUARY 1965

or Standards Binder Subscription Service

Individual Copies Individual copies of the following American Standards and a loose-leaf binder containing a complete set of all SMPTE-sponsored American Standards and SMPTE Recommended Practices can be purchased from the American Standards Association, Inc., 10 East 40 St., New York, N. Y. 10016 (212 MU 3-3058).

Those who would like to keep their Standards Binder up to date can, for an annual fee, avail themselves of a subscription service. The service will supply all approved American Standards and Recommended Practices which are sponsored by the SMPTE and which are validated during the calendar year. Proposed American Standards and Proposed SMPTE Recommended Practices are published in the Journal and are not included in the subscription service. A complete binder may be purchased with the subscription service. Write to SMPTE for detailed information regarding this service.

Apertur	Subject es, Camera	Std. No. Journal	I	Subject Film Usage, Camera	Std. No.	Journal
				8mm	PH22 21-1064	Dec 1964
16		BU99 7 1064 July 1064		16 3D	DU02 0 1000	Dec. 1904
lomm	• • • • • • • • • • • • • • • • • • • •			10mm, 2K	.PH22.9 ~1956	- June 1950
35mm		PH22.59-1954*Sept. 1954				Sept. 1964 <sup>1</sup>
		Sept. 1964 <sup>1</sup>		16mm. 1R	PH22.15-1955*	Sept. 1955
America	. Printer	• •		,,		Man 10631
Apertury				25	<b>D1</b> (00 0 0000	WIAY 1903-
16mm	Contact (positive				.PH22.2 -1961	Nov. 1961
	from negative)	PH22.48-1956* June 1956				
		Feb 19641	1	Film Usage, Projector		
	0	1 CD. 1704		,		-
16mm	Contact (reversal			8mm	.PH22.22-1964	Dec. 1964
	dupes)	PH22.49-1946*Apr. 1946*		16mm, 2R	PH22.10-1964	Dec. 1964
		R1955 Feb. 1964 <sup>8</sup>		16mm. 1R.	PH22.16-1955	Sept 1955
35mm	to 16mm (16mm			······, ······		Man. 104 21
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		BU00 46 10468 4 1046		16	DITOS A LASS	WIAY 1903
	positive prince)	FH22.40-1946 Apr. 1946		35mm	.PH22.3 -1961	July 1961
		K1959		35mm (Anamorphic)	PH22.103-1957*	'Mar 1957
35mm	to 16mm (16mm					Oct 19641
	dune negative)	PH22 47-1946* Apr. 1946		lound		000. 1701
	dabe negative)					
		R1959		Photographic		
16mm	to 35mm Enlargemen	t		16mm	PH22 41-1957*	Aug 1957
	Ratio.	PH22.92-1953* Jan. 1953		16	DU00 40 10571	INT 1057
		R1959		<b>J</b> Jimn	.FH22.40-1957	JAOA' 1321
25	D.I. Diana	K1333		35mm Double Width Push-	•	
35mm	Release Picture-			Pull, Normal Centerline.	. PH22.69-1960	Nov. 1948
	Sound Continuous					Dec 19604
	Contact	PH22.111-1958* June 1958		25 Devil 1 MC Ist D -1		Dec. 1900-
		O-+ 10(4)		somm Double width Push-	·	
		Oct. 1904.		Pull, Offset Centerline	. PH22.70-1960	Nov. 1948
Aperture	s, Projector					Dec. 1960*
· •		DITOD 00 10/78 Aug 10/7		Magnetic		
omm.	• • • • • • • • • • • • • • • • • • • •	. PH22.20-1957 - Aug. 1957				
		Aug. 1964 <sup>1</sup>		omm		
16mm.		PH22.8 -1957* Aug. 1957		Stripe	.PH22.88-1963	June 1963
		Dec 19641		Reproducing Character-		
15		DU00 69 105480 1054		istic	PH22 134-1963	Luly 1963
Jamm	•••••	FH22.56-1954 Sept. 1954		Cound Dourd	DI100 107 1070	N 10/2
		Sept. 1964 <sup>1</sup>		Sound Record	PH22.135-1962	Nov. 1962
35mm	(Anamorphic	•		lómm		
	2 55-1)	PH22 104-1957*Mar 19571		30 Mil-Stripe	PH22.101-1963	June 1963
	<b>2</b>			50-Mil Mag-optical		
		Jan. 1964•		Suite	DITOS LOS LACS	
35mm	(Anamorphic			Stripe	PH22.12/-1962	Nov. 1962
	2.35:1)	PH22.106-1957* Dec. 1957		100-Mil Stripe	. <b>PH22.87–1958*</b>	: June 1958
		Sept 19641		•		Dec. 19641
		Jept. 1904-		200-Mil Strine	DU09 07 1064	Man 1064
Film Dim	ensions†				DI100 .00 .000	MIAL. 1704
Dimen	tions for:			fomin, renorated 8mm.	PR122.136-1963	June 1903
16	Defense 1 Com OD			Picture-Sound Separation.	PH22.112-1958	*June 1958
iomm,	Perforated 8mm, 2R-			35mm		
	1500PH22,17-1	.954*May 1954, Aug. 19621		Four 100-Mil Records	PH22 108-1958	Iune 1958
16mm.	1R-2994	PH22.109-1958* Aug 1958		Four Decords	11144.100-1550	June 1750
		Oct 10641		rour Records,		
16	TD 2000			Release Prints	PH22.137-1963	Jan. 1964
ronni,	IR-3000	.PH22.12-1954* Jan. 1954		35/17½mm		
		Aug. 1962 <sup>1</sup>		1 or 3 200-Mil Records	PH72 86-1962	May 1962
16mm.	2R-2994	.PH22.110-1958* Aug. 1958				
		Oct 10641		Television		
16mm	2P. 3000	DU00 6 1062+ L = 1061		Toologia A		
rouun,	215000	rn22.5-1953* Jan. 1954		image Area		
		Aug. 1962 <sup>1</sup>		16mm Film	.PH22.96-1963	Oct. 1963
32mm,	2R-2994	PH22.141 Sept. 19631		35mm Film	PH22.95-1963	Oct. 1963
32mm.	2R-3000	PH22 71-1957*Mar 1057		Slider and Onserver	PU00 04 1064	1054
				Shues and Opaques	. 1 1122.94-1994	NIAY 1934
27	15.0004	Sept. 1963.				Dec. 1960*
52mm,	4R-2994	PH22.142 Sept. 19631		16mm Projector, Monochro	me	
32mm,	4R-3000	PH22.72-1957 Mar. 1957		Film Chains Full Storage		
-		Sept 10631		Basis	PH22 91-1055*	Ane 1955
35mm	Perforated 32mm	Sept. 1705			D1100 10(1	Apr. 1933
	2D 2004			tourn intermittent Projecto	rPH22.125*	Oct. 19001
	41 - 6994	rn22.73-1958" June 1958		Density and Contrast		
	2K-3000	PH22.138 Aug. 1962 <sup>1</sup>		Range, Films and Slides		
35mm.	BH-1866.	PH22.93-1964 Dec. 1964		(SMPTE Recommended	Practice	
35mm.	BH-1870	PH22 34 1064 Dec 1064		PP 7_1069\		Mar. 1042
35	CS-1970	DIG0 100 1001 DCC. 1904		RI /-1304)	· • • • • • • • • • • • • • • • • • • •	wiay 1902
35	DI 1070	.rn22.102-1964 Dec. 1964		Sale Action Area (SMPTE		
jumm,	DH-18/0	PH22.1-1964 Dec. 1964		Recommended Practice	RP 13-1963)	Dec. 1963
Jomm,	KS-1866	PH22.139-1964 Dec. 1964		Safe Title Area (SMPTE		
35mm.	KS-1870	PH22 36-1964 Dec 1964		Recommended Provide	DD 9-1061	1.1. 1041
65mm	KS.1844	DIAG 141 0 1004		Accommended r ractice	WT 0-1301)	. July 1901
65	KG 1070	PH22.145 Uct. 1964		2x2 Slide Mount (SMPTE		
oomm,	NO-18/0	PH22.118-1961 Mar. 1961		Recommended Practice	RP 9)J	an 1961 <sup>1</sup>
، umm,	Perforated 65mm.			Slides and Transparencies	,	
	KS-1870	PH09 110-1061 Man 1041		for TV	DU00 144	1 10641
		A AAAAAA IIJ-IJUI WIAF. 1901		IUT IV		APE. 19041

Society of Motion Picture and Television Engineers 9 East 41st St., New York, N. Y. 10017 (212) TN 7-5410 Cables: Somopict

	Subject	Std. No.	Journal
Test Fil	lms		
DL			
rhote	ographic	D1100	
10mm	+00-Cycle Signal Level	rH22.45-1962	Nov. 1962
	5000-Cycle Flutter	.PH22.43-1961	July 1961
	5000-Cycle Leans E		
	7000-Cycle 5 Sound F	Jeasing	
	• • •	PH22.42-1962	May 1962
	Buzz-Track	PH99 47-1042	fune 1063
	Multiference	DU00 44 1003	
	Staturequency (SMD		FED. 1905
	Sound Projector (SMP	I.E.	
	Recommended Prac	tice	
	<b>RP 18–1964</b> )	• • • • • • • • • • • • • • • • • • •	. Nov. 1964
	Theater Test Reel	.PH22.79-1950	<ul> <li>Apr. 1950</li> </ul>
	Scanning Beam, Labor	a- R195	6
	tory Type (corrected	X22 80-1950	Nov 1952
35000	1000-Cycle Balancing	PH22 67-1960	Nov. 1948
J J	root-cycle barancing.	.1 1144.0/-1900	10V. 1940
	7000 0 1 0 1		Oct. 1960*
	7000-Cycle Sound		
	Focusing	PH22.61-1963	July 1963
	9000-Cycle Sound		
	Focusing	PH22.62-1960	Nov. 1948
			Oct 19604
	Buzz Track	DU00 60-1069	Mar. 1062
	Duzz-Hack	. 1 1144.00-1904	WIAY 1902
	Scanning Beam,		
	Service Type	.PH22.65-1948	Nov. 1948
		R195	3
	Theater Test Reel	.PH22.60-1959	Nov. 1948
			Nov 19594
Magn	etic		
8	Azimuth	DU00 100-1000	Nov. 1062
0mm	A21muth	. P M 22.129-1902	NOV. 1902
	400-Cycle Signal Level	PH22.130-1962	Nov. 1962
	Flutter	PH22.128-1962	Nov. 1962
	Multifrequency	. PH22.131-1962	Nov. 1962
16 <i>mm</i>	Azimuth Alignment.	PH22.114-1959	July 1959
	Multi-Azimuth	PH22 126-1961	Nov 1961
	400-Cycle Signal Level	PH79 139-1063	Tune 1963
	Flume	1 1124.1J2-130J D1100 112 1060#	June 1905
	Flutter	H22.113-1958	Jan. 1959
	Multifrequency	PH22.140 S	Sept. 19631
35 <i>mm</i>	Azimuth Alignment	.PH22.99-1955*	May 1955
	Flutter	.PH22.98-1963	Oct. 1963
Test Me	thade timm Sound Di	varian	
1000.000	thous, rolling sound Di	NOTHOL	
Cross	Modulation, Variable-		
Are	<b>a</b>	PH22.52-1960	Oct. 1954
			Dec. 19604
Intern	nodulation Variable-		
Der	aiter	PH22 51-1061	f 1061
	arcy	11122.31-1301	July 1901
Test Pla	te		
Resolu	ition Target,		
16m	m Projector	PH22.53-1953*	fav 1953
			Dec 19643
Video N	Cannetic Tane Recordi-		
Leed IV	-sacae rape necordi	** Cop a +aca	Dec 10/2
Leade			Dec. 1903
Modu	ation Levels (SMPTE	Kecommended	-
Рга	ctice RP 6-1960)		Dec. 1960
Patch	Splices (SMPTE Recom	mended Practice	
RP	5-1964)		Apr. 1964
Record	ds. Characteristics of Aud	lio	
		C08 2-1062	Dec 1063
D	Dimensiona Video A		JCC. 1703
A COLO	Limensions, video, Au	and and	
_ Ira	cking Control		Apr. 1964
Record	<ol> <li>Fracking Control (SM)</li> </ol>	IPTE	
Rec	ommended Practice RF	16-1964)	May 1964
Reels.			May 19631
Signal	Specifications for Aligne	nent Tape	
/01/	PTF Recommended B	antine	
DP	10-1060	AUTUC	T.J., 10/2
C. RP	10-1902)		JULY 1902
Speed.			Dec. 1963
Tape l	Dimensions	C98.1-1963	Dec. 1963
Tape	Vacuum Guide		
(SM	PTE Recommended Pr	actice	
RP	11-1962)	1	Mar 1962
~~~		• • • • • • • • • • • • • • • • •	
MISCEL	LANEOUS		
Cores fo	r Raw Stock Film		
16		DUGG 20 10C+	\fa= 10/4
10mm		F F122.38-1964	VIAL 1904
Jomm		r fi22.37–1963	Jan. 1964
Density	Measurements		
Calibr	ation of Densitometers (S	SMPTE	

Subject	Std. No.	Journal
<b>Recommended</b> Practice		•
RP 15-1964	· · · · · · · · · · · · · · · · · · ·	Apr. 1964
Spectral Diffe	PH22.117-1960	Dec. 1960
Iran mission	PH22.27-1960	Mar. 1948
		Oct. 19604
Edge Numbering, 16mm Film	DU00 02 1050	N. 1052
Luge Numbering, tomm rum	FR22.83-1952	-Nov. 1952
Film Length Rom Comers Same	.1	Dec. 1964
(25 ft Capacitu)	DU00142	0-1 10(2)
(25 ft. Capacity)		Oct. 1963.
rum winding		
16mm, 1R	PH22.75-1953	Feb. 1954
• • • • • •	R196	1
Lamps, 16mm and 8mm Project	ctors	
Base-Up Type	. PH22.84-1964	July 1964
Base-Down Type	. PH22.85-1964	July 1964
Lens -		
Aperture Calibration	PH22.90-1964	Tune 1964
Focal Lengths.		5 and 1704
Markings, 35mm	PH22.28-1958*	June 1958
		• une 1750
Focus Scales, 16mm and 8mm		
Cameras	PH22.74-1951*	Sept. 1949
•	R1957	Oct. 19631
Lens Mounts		
16 & 8mm Cameras	PH22.76-1960	Feb. 1960
High-Speed Motion-Picture Ca	umeras	
(SMPTE_Recommended Pr	actice	
	R1964	
RP 3-1957)		Aug. 1957
Nomenclature, Film		
(Sections 1-4)	PH22.56-1961	July 1961
(Sections 5-7)P	H22.56a-1964 N	Mar. 1964
Photometric Performance.		
Incandescent Lighting Units		
(IES-SMPTE Recommended	d Prac-	Sept. 1958
tice RP 4-1958)*		May 1959
Reels		,,
8mm	PH22 23-1958*	Aug 1958
16mm	PH22.11-1953*	Sept 1953
35mm.	7.22 4-1941*	Mar 1941
		Aug. 19631
Reel Spindles 16mm	PH99 50_1060	Dec 1057
Acci opinaics, round	1144.30-1300	Dec. 1952
Release Prints 35mm	7.99 55-1947*	Mar 1948
Rescale Films, 55mm	DITAG 410 1	D . 10/4
Reversal Color Fum Speed		SEC. 1904.
Safety Film	PH22.31-1958*	Jan. 1959
Scene Change Cue	PH22.89-1958*.	June 1958*
•	S	cpt. 1964 <sup>3</sup>
Screen		•
Brightness, 35mm Motion		
Pictures	PH22.39-1953	Mav 1953
Withdrawn 1964		July 1964*
35mm Indoor TheatersP	H22.124-1961 S	Sept. 1961
35mm Review RoomsP	H22.133-1963	June 1963
Drive-In Theaters		
(SMPTE Recommended Pra	actice	
<b>RP 12–1962</b> )	<b></b>	July 1962
16mm Review RoomsP	H22.100-1955*	Feb. 1956
Sensitometric Strips (SMPTE Re	commended	
Practice RP14-1964		Apr. 1964
Splices, 16 & 8mm		
Laboratory Type	PH22.77-1952*	June 1952
· · ·	A	ug. 1964 <sup>1</sup>
Projection TypePl	H22.24–1952* J	lune 1952
	A	Aug. 1964 <sup>1</sup>
Spools, 8mm, 25-ft Capacity	H22.107-1964	June 1964
Sprockets		
16		
IOMM		(A)
(SMFIE Recommended h	Tactice RP-195	F-L 1050
35mm	K1963	CCD. 1950
Unsteadiness High Speed Come	4 1122.JJ-1902 -	141 ay 1902
(SMPTE Recommended P	a	
RP 17-1964)		May 1964

Under Committee review. R-Reaffirmed.
† Film dimension titles show film width, perforation pitch (without the decimal point) and a code designation for the perforation shape—BH KS DH CS (Bell & Howell, Kodak Standard, Dubray-Howell, CinemaScope)—or number of rows of perforations (1R, 2R or 4R), depending on which is the significant factor.
<sup>1</sup> Proposed standard or recommended practice. <sup>3</sup> To be withdrawn. <sup>4</sup> Notice of intended withdrawal.
<sup>4</sup> Essential technical content is included in the early publication date. The later date lists editorial or nontechnical changes agreed to by SMPTE engineering committees and subsequently incorporated in a revision of the standard.
<sup>4</sup> Appendix A. Technical Information on Lamps Used for Testing and Reporting Data, was omitted from the September 1958 issue since it was incomplete. <sup>4</sup> Notice of approved withdrawal.

## **APPENDIX D**

# AMERICAN STANDARDS ASSOCIATION

The following American Standards are reproduced by permission of the ASA, copyright holder. Copies may be purchased from the American Standards Association, 10 East 40th Street, New York, N.Y. 10016.



Convergent 1961 by the American Standards Association, Incorporated 28 East 40th Street, New York 10016 Printed in D.S.A. ASALMIZEL, SU

Page 2 of 2 pages

#### APPENDIX

{This Appendix is not a part of American Standard Dimensions for 35mm Motion-Picture Pilm, K5-1870, PM22.36-1964, but is included to facilitate its use.]

A1. The dimensions given in this standard represent the practice of film manufacturers in that the dimensions and tolerances are for film stock immediately after perforation. The punches and dies themselves are made to tolerances considerably smaller than those given, but since film is a plastic material, the dimensions of the slit and perforated film stock never agree exactly with the dimensions of the slitters, punches and dies. Film can shrink or swell due to loss or gain in moisture content or can shrink due to loss of solvent. These changes invariably result in changes in the dimensions during the life of the film. The change is generally uniform throughout a roll.

A2. It will be noted that among the various standards for slitting and perforating film stock there are often two standards which seem much alike in wording. The difference lies in the longitudinal pitch which is either 0.1870 in. or 0.1866 in. In general, the longerpitch is for print stock and the shorter pitch is for negative stock.

The choice of pitch for negative motion-picture films depends, within certain limits, on the type of printer to be used. Where step-printers are used, and the film is stationary when exposed, the choice of pitch is not strictly limited. Where the film moves continuously over a cylindrical surface at time of printing (spracket-type printer), there are three major considerations involved in choosing the pitch. These considerations are: {1} the spracket diameter, {2} the film thickness, {3} the film shrinkage and the rate at which shrinkage occurs.

Maximum steadiness and definition are secured on a sprocket-type printer when the negative stack is somewhat shorter in pitch than the positive stack in the approximate proportion of the thickness of the film to the radius of curvature. For printing on a 64-tooth 35mm sprocket {circumference of about 12 in.} with film 0.0055 to 0.0065 in, thick, the optimum pitch differential is 0.3 percent. The use of the ideal pitch differential for the negative would minimize slippage between the positive stock and negative during the printing operation, thus reducing the amount of blurring and jumping of horizontal lines in the picture or sound image. (This error is to be differentiated from the jump caused by nonuniformity of successive pitches, Dimension 8.)

Experience has shown that the average pitch, Dimension 1, of the negative can vary  $\pm 0.1$  percent from the ideal pitch, which is 0.3 percent shorter than the positive stack, without blurring of picture and sound image being easily detected.

For many years this desired difference in pitch was coused by the shrinkage of the negative film during processing and aging. Current film bases shrink less than the earlier ones and hence a shorter initial pitch becomes desirable. To satisfy this requirement for picture or sound negatives, it is common manufacturing practice to aim for a pitch value 0.2 percent shorter than the positive stock onto which they will be printed. The additional shrinkage that occurs during processing and the aging that takes place before the release prints are made then brings the pitch differential close to the optimum and desired value of 0.3 percent. Accordingly, the pitch chosen for the negative stock is 0.1866 in.

Low-shrink negative film perforated to these dimensions should not thereafter shrink appreciably more than 0.2 percent under normal use conditions, and for a reasonable life span, so that the optimum pitch differential from the positive stock of  $0.3 \pm 0.1$  percent is maintained. (The film should be measured after equilibration with air at 70 F and 55 percent relative humidity or at the conditions prevailing at the time of perforating.)

A3. The uniformity of pitch, hole size, and margin (Dimensions B, C, D, and E) is an important variable affecting steadiness. Variations in these dimensions, from roll to roll, are of little significance compared to variations from one sprocket hole to the next. Actually it is the maximum variation from one sprocket hole to the next within any small group of consecutive perforations that is important.

PH22.36-1964



Luppight 1965 by the American Standards Association, Incorporated 10 East 40th Street, Now York, N. Y. 10816 Printed in USA

Page 2 of 3 Page

#### Appendix

(This Appendix is not a part of American Standard Dimensions for Jámm Mation Picture Film, 28.3000, PH22.5.1964, but is included to facilitate its use)

A1. The dimensions given in this standard represent the practice of film manufacturers in that the dimensions and tolerances are for film stack immediately after perforation. The punches and dies themselves are made to tolerances considerably smaller than those given, but since film is a plastic material the dimensions of the slit and perforated film stock never agree exactly with the dimensions of the slitters, punches and dies. Film can shrink or swell due to loss of gain in moisture content or can shrink due to loss of solvent. These changes invariably result in changes in the dimensions during the life of the film. The change is generally uniform throughout a roll.

A2. It will be noted that among the various standards for slitting and perforating film stock there are often two standards which seem much alike in wording. The difference lies in the longitudinat pitch which is either 0.2994 in. or 0.3000 in. In general, the longer pitch is for print stock and the shorter pitch is for negative stock.

The choice of pitch for nagative motion-picture films depends, within certain limits, on the type of printer to be used. Where step-printers are used, and the film is stationary when exposed, the choice of pitch is not strictly limited. Where the film maves continuously over a cylindrical surface at time of printing (spracket-type printer), there are three major considerations involved in choosing the pitch. These considerations are: (1) the spracket diameter, (2) the film thickness, (3) the film shrinkage and the rate at which shrinkage occurs.

Maximum steadiness and definition are secured on a sprocket-type printer when the negative stock is somewhat shorter in pitch than the positive stock in the approximate proportion of the thickness of the film to the radius of curvature. For printing on a 40-tooth 16mm spracket (circumference of about 12 in.) with film 0.0055 to 0.0065 in. thick, the optimum pitch differential is 0.3 percent. The use of the ideal pitch differential for the negative would minimize slippage between the positive stock and negative during the printing operation, thus reducing the amount of blurring and jumping of harizontal lines in the picture or sound image. (This error is ta be differentiated from the jump caused by nonuniformity of successive pitches, Dimension 8.)

Experience has shown that the average pitch of the negative can vary + 0.1 percent from the ideal pitch, which is 0.3 percent shorter than the positive stock, without blurring of picture and sound image being easily detected.

For many years this desired difference in pitch was caused by the shrinkage of the negative film during

processing and aging. Current film bases shrink lets than the earlier ones and hence a shorter initial stich becomes desirable. To satisfy this requirement for pictureor sound-negatives, it is common manufacturing practice to aim for a pitch value 0.2 percent shorter than the positive stock onto which they will be printed. The additional shrinkage that occurs during processing and the aging that takes place before the release prints are made then bring the pitch differential close to the optimum and desired value of 0.3 percent. Accordingly, the pitch chosen for the negative stock is 0.2994 in.

tow-shrink negative film perforated to these dimensions should not thereafter shrink appreciably more than 0.2 percent under normal use conditions, and for a reasonable life span, so that the optimum pitch differential from the positive stock of 0.3 ±. 0.1 percent is maintained. (The film should be measured after equilibration with air at 70 F and 55 percent relative humidity or at the conditions prevailing at the time of perforating.)

A3. The uniformity of pitch, hole size, and margin (Dimensions B, C, D, and E) is an important variable affecting steadiness. Variations in these dimensions, from roll to roll, are of little significance compared to variations from one sprocket hole to the next. Actually it is the maximum variation from one sprocket hole to the next within any small group of consecutive perforations that is important.

A4. The optimum width for 16mm film (which often goes through channels of fixed size) is controlled by the shrinkage characteristics of the films involved. Thus in times past there have been standards for the width of 16mm stock of the "usual" shrinkage and for stock of "low shrinkage" characteristics. The purpose was to obtain films of approximately the same width regardless of the type of film base during their useful life. This standard is based on the values adapted to "low-shrink" film base since nearly all films now manufactured in the U.S. meet the definition naied below.

For the purpose of choice of width, low-shrinkage film base is film base which when coated with emulsion and any other normal coating treatment, perforated, kept in the manufacturer's normal commercial packings for six months at 65 to 75 F, exposed, processed and stored exposed to air for a period not to exceed 30 days at 65 to 75 F and 50 to 60 percent relative humidity, and measured under like conditions of temperature and humidity, shall have shrunk not more than 0.2 percent from its original dimension at the time of perforating.

#### Page 3 of 3 pages

This definition of low-shrinkage film stock has been found by experience to be useful as a guide to film monufacturers in slitting their stock. Departure from this definition shall not be cause for rejection of the stock. Note that this definition of shrinkage differs from the criterion applying to the choice of longitudinal pitch, where greater periods of time are involved and where short-time tests can be deceptive. Allowance has been made in arriving at these values for the common tendency of film to expand when exposed to high relative humidity. Allowance should be made for this factor in equipment design and in no case should 16mm equipment fail to accommodate a film of 0.630-in. width.

**A5.** This film is to be made on safety base complying with American Standard Specifications for Safety Photographic Film, PH1.25-1956 (Reaffirmed 1962).

PH22.5-1964

# **APPENDIX E**

# **PERFORATION DIMENSIONS**

The following excerpts are reproduced by permission of Eastman Kodak Company. Copies of publication P-29, <u>Technical Data on Film Specification Numbers, Spools, Cores,</u> <u>Dimensions and Perforations</u>, may be obtained from Eastman Kodak Company, Department 454, 343 State Street, Rochester, New York 14650.

# PERFORATION DIMENSIONS 16 mm-35 mm-70 mm



Perforation Type									
Dimension	Bell &	Howell	Kodak S	Standard	16 Mil	limeter	Tolerances ±		
	Inches	mm	Inches	mm	Inches	mm	Inches	mm	
C D	0.110 0.073	2.794 1.854	0.110 0.078	2.794 1.981	0.072 0.050	1.829 1.270	0.0004 0.0004	0.010 0.010	
H* R	0.082	2.08	0.020	0.51	0.010	0.25	0.001	0.03	

\*Dimension H is a calculated value.

# FILM DIMENSIONS, 16 mm





Perforated one edge

Perforation Type and ANSI Number										
Dimension	1R- (PH2	2994 2.109)	1R-: (PH2	3000 22.12)	2R- (PH2	2994 2.110)	2R- (PH	3000 22.5)	Tolerances ±	
	Inches	mm	Inches	mm	Inches	mm	Inches	mm	Inches	mm
A* B	0.628 0.2994	15.95 7.605	0.628 0.3000	15.95 7.620	0.628 0.2994	15.95 7.605	0.628 0.3000	15.95 7.620	0.001 0.0005	0.03 0.013
E F	0.0355	0.902	0.0355	0.902	0.0355 0.413	0.902 10.49	0.0355 0.413	0.902 10.49	0.0020 0.001	0.051 0.03
G (max) L†	29.94	760.5	30.00	762.0	0.001 29.94	0.03 760.5	0.001 30.00	0.03 762.0	0.03	0.8

.

\*This dimension also represents the unperforated width. \*This dimension represents the length of any 100 consecutive perforation intervals.

# FILM DIMENSIONS, 35 mm



Perforation Type and ANSI Number													
Dimension	BH-1866 (PH22.93)		BH-1870 (PH22.34)		KS-1866 (PH22.139)		KS-1870 (PH22.36)		Tolerances ±				
	Inches	mm	Inches	mm	Inches	mm	Inches	mm	Inches	mm			
A* B	1.377 0.1866	34.975 4.74	1.377 0.1870	34.975 4.75	1.377 0.1866	34.975 4.740	1.377 0.1870	34.975 4.750	0.001 0.0005	0.025 0.013			
E F	0.079 0.999	2.01 25.37	0.079 0.999	2.01 25.37	0.079 0.999	2.01 25.37	0.079 0.999	2.01 25.37	0.002 0.002	0.05 0.05			
G (max) L†	0.001 18.66	0.03 474.00	0.001 18.70	0.03 474.98	0.001 18.66	0.03 474.00	0.001 18.70	0.03 474.98	0.015	0.38			

Perforation Type and ANSI Number												
Dimension	Perf. 32 mr (PH2	n, 2R-2994 2.73)	Perf. 32 mi (PH2	n, 2R-3000 2.138)	Tolerances $\pm$							
	Inches	mm	Inches	mm	Inches	mm						
A* B	1.377 0.2994	34.98 7.605	1.377 0.3000	34.98 7.620	0.001 0.0005	0.03 0.013						
E F	0.096 1.041	2.44 26.44	0.096 1.041	2.44 26.44	0.002 0.002	0.05 0.05						
G (max) L†	0.001 29.94	0.03 760.5	0.001 30.00	0.03 762.0	0.03	0.8						

.

\*This dimension also represents the unperforated width. †This dimension represents the length of any 100 consecutive perforation intervals.